



*Nevada 750*

*Nevada 350*



*giovani emozioni*



# Nevada 750 350





*In the classic tradition of custom styled motorcycles, Moto Guzzi presents the Nevada. The Nevada satisfies the most demanding rider. Ride the Nevada around town commuter and weekend cruiser or experience the pleasure of running with the wind, the warm purr of the even reliable V-twin as you seek a new horizon for your holiday destination. Whatever you choice the enjoyment is all yours.*







# MOTO GUZZI

## TECHNICAL SPECIFICATIONS

(Data between brackets refer to NEVADA 350)

**Engine** 90° V-twin, 4-stroke, "Nigucil" cylinder lining

**Displacement** 744 (346,2) cc

**Bore and stroke** 80 x 74 (66 x 50,6) mm

**Output** 35 (22) kW (48 (30) HP) at 6200 (6200) r.p.m. [DIN rules]

**Max torque** 59,44 (30) Nm [6,06 (3,1) Kgm]

at 3200 (6200) r.p.m. [DIN rules]

**Fuel Delivery** two Dell'Orto carburetors PHBH 8D-BS 30

(PHBH 28 B)

**Ignition** electronic Motoplaf double pick-up

**Compression ratio** 9,6 : 1 (10,6 : 1)

**Timing** C.H.V., 2 valves per cylinder

**Lubrication** by pressure pump

**Starting** electric

**Clutch** single plate, dry type

**Gearbox** 5-speed, constant mesh gears

**Transmission** primary by gears, secondary by cardan shaft with universal joint and bevel gear

**Frame** tubular duplex cradle, disassemblable

**Suspensions** front Moto Guzzi hydropneumatic telescopic fork with pressure equalizer

rear swinging fork, light alloy die-casting, with two hydraulic shock absorbers

**Wheels** spokes with light alloy rim

**Tyres** front 100/90 V18 (100/90 H18 or V18) Tube type

rear 130/90 V16 (130/90 H16 or V16) Tube type

**Brakes** front dual discs Ø 270 mm, rear single disc Ø 260 mm

**Electrical system** 12V, 14V-20A alternator; 12V-24Ah (18Ah) battery

**Instrument panel** speedometer, rev-counter and warning lights

**Fuel tank capacity** 10,5 (10) l [3,63 (3,52) imp. gal.]

**Fuel consumption** 5,4 (5,5) l x 100 Km [CUNA rules]

**Max speed** 165 (150) Km/h approx [103 (93) mph]

**Dry weight** 177 (170) Kgs [390 (375) lb]



**GBM SpA** 22064 Mandato del Lario (Como) - Via E.V. Parodi, 57  
Tel. (0341) 70.31.11 - Telex (0341) 70.92.20

It is recommended to use original fittings from MOTO GUZZI, which are tested in the factory and supplied as optional.

THE ILLUSTRATIONS AND DESCRIPTIONS GIVEN IN THIS LEAFLET ARE INTENDED AS A GENERAL GUIDE ONLY, AND MUST NOT BE TAKEN AS BINDING. THE COMPANY, THEREFORE, RESERVES THE RIGHT TO MAKE, AT ANY MOMENT AND WITHOUT NOTICE, ANY CHANGES IT THINKS NECESSARY TO IMPROVE THE MOTORCYCLE OR TO MEET ANY REQUIREMENTS OF MANUFACTURING OR COMMERCIAL NATURE.